

FRONT ELEVATION

SIDE ELEVATION

CONSTRUCTION SPECIFICATION

IP42 200A INSULATED LINK BOX:
INSULATED ENCLOSURES. WALL MOUNT. LIFT OFF LIDS. CLEAR COVER, W360mm x H360mm x D174mm

COPPER LINKS:

4 x W25mm x H165mm H6.3mm (RATED AT 392A) Cu WITH 4 x M8 BOLTS. LINKS MOUNTED ON BUSBAR SUPPORT AT 75mm CENTRES.

QTY 8, BUSBAR INSULATORS PART NO. SM-35


LABEL DETAILS:

1 x ELECTRICAL HAZARD LABEL
1 x AS3439.1 LABEL

CONTRACTOR TO TAKE NOTE OF THE MIN & MAX DISTANCES WHEN INSTALLING, AS PER THE NSW SERVICE AND INSTALLATION RULES AND SUPPLY AUTHORITY REQUIREMENTS.

RISING MAIN CONNECTORS NOT SHOWN. RISING MAIN CONNECTORS ARE SUPPLIED UNINSULATED. BOVARA RECOMMENDS INSULATING RISING MAIN CONNECTERS AS PER AS3000.

COMPLIES TO AS3000, NSW SERVICE AND INSTALLATION RULES, AND AS3439.1

PROJECT -	CUSTOMER -	DRAWN by - DYLAN DONG	YOUR REF:	IP Rating : IP42
			COLOUR : GREY ENCLOSURES WITH CLEAR LIDS	FORM: FORM 1
DRAWING No. - LINK-2001	DATE - 01/06/2015	CHECKED by - NAS CHEDIAC	MATERIAL : 3mm POLYCARBONATE	WIDTH: 360mm
	102 WETHERILL ST NORTH SILVERWATER, NSW 2128 PH: 1300 268 272 Fax: 1300 272 862 Email: sales@bovara.com.au		SCALE : 1:5 @ A3	HEIGHT: 360mm
				DEPTH: 174mm