


FRONT ELEVATION



SIDE ELEVATION

CONSTRUCTION SPECIFICATION

IP30 630A METAL LINK BOX:
 1.5MM, ZINC ANNEALED STEEL, POWDER COATED COLOUR:
 ORANGE-X15 SMOOTH FINISH LIFT-OFF COVERS
 SEALABLE W400mm x H650mm x D240mm

6mm BAKELITE GLAND PLATES TOP & BOTTOM.


COPPER LINKS:
 4 x W40mm x H200mm x D10mm CU LINKS (RATED AT 858A)
 MOUNTED ON BUSBAR SUPPORT CONSTRUCTED FROM DENSIFIED
 WOOD, AT 75MM CENTRES.

LABEL DETAILS:
 1 x ELECTRICAL HAZARD LABEL
 1 x AS3439.1 LABEL

CONTRACTOR TO TAKE NOTE OF THE MIN & MAX DISTANCES
 WHEN INSTALLING, AS PER THE NSW SERVICE AND INSTALLATION
 RULES AND SUPPLY AUTHORITY REQUIREMENTS.

RISING MAIN CONNECTORS NOT SHOWN. RISING MAIN
 CONNECTORS ARE SUPPLIED UNINSULATED. BOVARA
 RECOMMENDS INSULATING RISING MAIN CONNECTERS AS PER
 AS3000.

COMPLIES TO AS3000, NSW SERVICE AND INSTALLATION RULES,
 AND AS3439.1

PROJECT -	CUSTOMER -	DRAWN by - DYLAN DONG	YOUR REF:	IP Rating : IP30
			COLOUR : X-15 ORANGE	FORM: FORM 1
DRAWING No. - LINK-630M	DATE - 01/06/2015	CHECKED by - NAS CHEDIAC	MATERIAL : 1.5mm GALVABOND STEEL	WIDTH: 400mm
	102 WETHERILL ST NORTH SILVERWATER, NSW 2128 PH: 1300 268 272 Fax: 1300 272 862 Email: sales@bovara.com.au		SCALE : 1:5 @ A3	HEIGHT: 650mm
				DEPTH: 240mm